

3620 / 3630 PULVI-MULCHER

3630 Pulvi-Mulcher

The 3630 Pulvi-Mulcher Series, which consists of three-section folding units, features working widths of 30' and 36'6". The 30' model weighs 80% more than the popular WL360 model for more clod crushing power. The 36'6" unit is the widest Pulvi-Mulcher ever offered by Brillion. Large 8" roller axles with heavy-duty bearings eliminate the traditional center bearing, improve reliability and reduce downtime. A choice of 20" notched ductile iron wheels, 20" crowfoot ductile iron wheels or 20" Optimizer® ductile iron wheels are available to accommodate specific soil conditions.



3620 Pulvi-Mulcher

The 3620 Pulvi-Mulcher Series, available in 21' working widths, was designed with many of the same features of the 3630, but the two-section folding design allows for a narrow transport width of 12'3". The 21' model also utilizes a hydraulic down pressure system for even machine weight distribution across the width of the machine. A two-row coil tine harrow is included in front of the rear roller to help level ridges left by the shanks. Heavy-duty wheel hubs coupled with the maintenance free lift system will provide years of trouble-free service.



BrillionTM
Farm Equipment

A LANDOLL PRODUCT

3630 Pulvi-Mulcher

- Designed for Improved Trash Flow Through the Machine
- Three Rows of Shanks on Overall 6" Spacing
- Two-Piece Edge Bent S-Tine Shanks for Better Leveling
- 25" Under Frame Shank Clearance
- 18" Between Shanks, Minimum of 24" Between Rows
- 2" Reversible Points
- Maximum Shank Operating Depth of 5"
- Hydraulically Actuated Spike Leveling Bar in Front of Rear Roller
- 8" Roller Axles
- 61mm Heavy-Duty Bearings
- Choice of 20" Notched Ductile Iron Wheels, 20" Crowfoot Ductile Iron Wheels or 20" Optimizer® Ductile Iron Wheels
- Rear Scrapers Standard on Notched Rollers
- Hitch Floats 10 Degrees Up, 20 Degrees Down
- Wings Float 10 Degrees Down
- Independent Hydraulic Tooth Depth Control
- Dual Transport Wheels
- (4) 380/55RX16.5 Tires
- Cat. III, IV or V Hitch
- Transport Height - 12'10"
- Transport Width - 19'
- LED Warning Lights & SMV Emblem
- Safety Chain Kit
- Powder Coat Paint

3620 Pulvi-Mulcher

- Designed for Improved Trash Flow Through the Machine
- Three Rows of Shanks on Overall 6" Spacing
- Two-Piece Edge Bent S-Tine Shanks for Better Leveling
- 25" Under Frame Shank Clearance
- 18" Between Shanks, Minimum of 24" Between Rows
- 2" Reversible Points
- Maximum Shank Operating Depth of 5"
- Two-Row Coil Tine Harrow in Front of Rear Roller
- 8" Roller Axles
- 61mm Heavy-Duty Bearings
- Choice of 20" Notched Ductile Iron Wheels, 20" Crowfoot Ductile Iron Wheels or 20" Optimizer® Ductile Iron Wheels
- Rear Scrapers Standard on Notched Rollers
- Hitch Floats 10 Degrees Up, 35 Degrees Down
- Wings Float 5 Degrees Down
- Independent Hydraulic Tooth Depth Control
- Dual Transport Wheels
- (4) 12.5LX15 FI Tires
- Cat. III, IV or V Hitch
- Transport Height - 13'4"
- Transport Width - 12'3"
- LED Warning Lights & SMV Emblem
- Safety Chain Kit
- Powder Coat Paint



220 N. Francis Street
P.O. Box 8
Brillion, WI 54110

Phone: 920.524.2220
Toll Free: 855.320.0373
Fax: 888.761.8568



www.facebook.com/landollag



Visit your local dealer today for more information on the Pulvi-Mulcher lineup from Brillion!

www.brillionfarmeq.com

3620/3630_1116_Z_xx